



*High Performance USB 3.0 C-mount
Microscope Camera*

Camera specifications	PC Camera resolution (MP)	6
	Camera resolution (n° of pixels: W x H)	2748x2200
	USB Signal output	USB.3.0
	Color / Monochrome	Color
	Sensor Size	1"
	Sensor Technology	CCD
	Sensor Type	SONY EXVIEW
	Rolling Shutter	Yes
	Image Format	5/4
	Pixel Size (µm)	4.54x4.54
	Frame rate full resolution (fps)	7.5@2748x2200
	Frame rate other resolution (fps)	14@2748x1092
	Dynamic range (DB)	62
	G sensitivity	1000mV at 1/30s
	Dark Signal	8mV at 1/30s
	ADC conversion	8 Bit - 12Bit
	Color Depth	1, 4, 8, 24 Bit
	Exposure time	0.06 msec - 1000 sec
	Binning	1x1
	IR filter	Yes
	IR filter range (nm)	380-650 (IR CUT)
	Camera Power	PC USB
	C-Mount	Yes
Dimensions (mm)	68 x 68 x 46	
Weight (Kg)	0.32	

Camera accessories	Calibration slide	Yes
	USB cable (1.8m)	Yes

Environment specifications	Working Temperature	-10°C up to +50°C
	Storage Temperature	-20°C up to +60°C
	Relative Humidity	30% to 80%
	Storage Humidity	10% to 60%

Operating System	OS	Windows 7
	OS	Windows 8
	OS	Windows 10 (32Bit)
	OS	Windows 10 (64Bit)
	OS	Osx (MAC Osx) starting from 10.7.5
	OS	Linux
Available Software	SW	PROVIEW
	SW	LITEVIEW
PC requirements	PC	CPU: Intel Core2 - 2.8GZ or higher
	PC	RAM: 2GB or more
	PC	USB 3.0
Warranty	Years	2